

Particle swarm optimization algorithm

Author: Michal Pluháček

Organization: FAI UTB

(c) 2011

Version : PSOBseWeight (See documentation for details)

PSO BASE with INERTIA WEIGHT

■ BODY

```

PSOBaseWeight[Cost_, Spec_, Ws_: 0.9, We_: 0.4] :=
Module[{CF, Specimen, dim, n, NP, c1, c2, RangeFrom, RangeTo, vMax, gBestVal,
  gBestPos, pBestVal, pBestPos, vfield, pop, fitness, i, j, k, wstart, wend},
  CF = Cost;
  Specimen = Spec;
  n = 50;
  dim = Dimensions[Specimen, 2][[1]];
  NP = dim * 10;
  c1 = 2;
  c2 = 2;
  wstart = Ws;
  wend = We;
  RangeFrom = Specimen[[All, 2, 1]];
  RangeTo = Specimen[[All, 2, 2]];
  gBestVal = CF[(RangeTo / 2)];
  gBestPos = RangeTo / 2;
  pBestVal = Table[CF[RangeFrom / 2], {NP}];
  pBestPos = Table[RangeFrom / 2, {NP}];
  pop = Table[Table[Random[Specimen[[dim, 1]],
    {Specimen[[dim, 2, 1]], Specimen[[dim, 2, 2]]}], {dim}], {NP}];
  vfield = Table[Table[0, {dim}], {NP}];
  Table[
    w = wstart - ((wstart - wend) * i) / n;
    Table[
      vfield[[j]] =
        w * vfield[[j]] + c1 * RandomReal[{0, 1}] * (pBestPos[[j]] - pop[[j]]) +
        c2 * RandomReal[{0, 1}] * (gBestPos - pop[[j]]);
      pop[[j]] = pop[[j]] + vfield[[j]];
      Table[
        If[pop[[j, k]] < RangeFrom[[k]] || pop[[j, k]] > RangeTo[[k]],
          pop[[j, k]] = RandomReal[{RangeFrom[[k]], RangeTo[[k]]}];
        , {k, 1, dim, 1}];
      fitness = CF[pop[[j]]];
      If[fitness < pBestVal[[j]],
        pBestVal[[j]] = fitness; pBestPos[[j]] = pop[[j]];
      If[fitness < gBestVal, gBestVal = fitness; gBestPos = pop[[j]]];

      , {j, 1, NP, 1}];
    , {i, 1, n, 1}];
  Return[{gBestVal, gBestPos}];
];

```

■ Usage example

■ Cost Function definition

Note: Input to function is array of numbers. Output is single number.

```
schwefel[vstup_] := Module[{pole, i},
  pole = vstup;
  If[VectorQ[pole] != True, pole = {pole, 0}];
  Table[
    pole[[i]] = -pole[[i]] * Sin[Sqrt[Abs[pole[[i]]]]], {i, 1, Length[pole]};
  Return[Total[pole]];
]
CF = schwefel;
```

■ Specimen definition

Note : Specimen format $\{\{Type, \{From, To\}\}\}$

```
Specimen = {{Real, {-512, 511}}, {Real, {-512, 511}}};
```

or (these are equivalent):

```
Specimen = Table[{Real, {-512, 511}}, {2}];
```

■ Running the algorithm

Format: **PSOBaseWeight**[*Cost function, Specimen, Starting weight*, Ending weight**]

* not required

Result format: $\{gBest\ Value, \{gBest\ Position\}\}$

```
result = PSOBaseWeight[CF, Specimen, 0.9, 0.4]
{-836.851, {423.561, 422.423}}
```

Getting gBest value only

```
result[[1]]
-836.851
```

Getting gBest positon only

```
result[[2]]
{423.561, 422.423}
```